
Material Safety Data Sheet

PRODUCT NAME: LOG BUILDER
PRODUCT COLORS: Dark Brown, Tan, Woodtone

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Sashco, Inc.
ADDRESS: 10300 E. 107th Place, Brighton, CO 80601
EMERGENCY PHONE: 1-800-535-5053
INFORMATION PHONE: 1-800-767-5656
DATE REVISED: January 4, 2013
REPLACES: September 16, 2010
REASON REVISED: Annual Review
CODE IDENTIFICATION: LBR – High Performance Acrylic Latex Caulk
PRODUCT IDENTIFICATION: Log Builder

Health	HMIS Ratings		PPE
	Flammability	Reactivity	
1	0	0	B

===== SECTION II - COMPOSITION =====

INGREDIENT	CAS#	WT.%	TLV	PEL	VAPOR PRESSURE
<i>Ethylene Glycol</i>	000107-21-1	1.0-3.5	50PPM	50PPM	0.12 mmHg @ 25°C

* The Threshold Limit Value (TLV) is the time weighted average (TWA) to which it is believed that most workers may be exposed 8-10 hours per day, 40 hours per week, without adverse health effects.
This chemical is subject to the reporting requirements of section 313 of SARA Title III.

===== SECTION III - PHYSICAL DATA =====

SPECIFIC GRAVITY (H₂O=1): 1.14
PERCENT VOLATILE BY WEIGHT (%): 33-35%
EVAPORATION RATE (WATER=1): >1
SOLUBILITY IN WATER (cured film): Negligible
APPEARANCE AND ODOR: Fluid Paste, Slight ammonia odor, variety of colors
BOILING POINT (°F): N/A
VAPOR PRESSURE (mm Hg.): N/A
VAPOR DENSITY (AIR=1): N/A

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (°F): N/A
FLAMMABLE LIMITS: N/A
EXTINGUISHING MEDIA: Normal procedures
SPECIAL FIRE FIGHTING PROCEDURES: Direct water spray may cause frothing.
UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

===== SECTION V - HEALTH HAZARD DATA =====

THRESHOLD LIMIT VALUE: N/A
EFFECTS OF OVEREXPOSURE: None known

EMERGENCY AND FIRST AID PROCEDURES: If product has been ingested, administer two glasses of water and contact a physician. If material comes in contact with eyes, rinse thoroughly for at least 20 minutes. If irritation persists, contact a physician.

===== SECTION VI - REACTIVITY DATA =====

STABILITY: Stable
INCOMPATIBILITY: None known
HAZARDOUS DECOMPOSITION PRODUCTS: None known
HAZARDOUS POLYMERIZATION: Will not occur

===== SECTION VII - SPILL OR LEAK PROCEDURES =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
Wipe or scrape up and dispose. No special precautions are required.

WASTE DISPOSAL METHOD:
Dispose in a sanitary landfill or incinerate according to local, state, and federal regulations.

===== SECTION VIII - SPECIAL PROTECTION INFORMATION =====

RESPIRATORY PROTECTION: None needed
VENTILATION: Local exhaust, general
PROTECTIVE GLOVES: Not normally needed. See Section V.
EYE PROTECTION: Not normally needed. See Section V.
OTHER PROTECTIVE EQUIPMENT: None required

===== SECTION IX - SPECIAL PRECAUTIONS =====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: None known
OTHER PRECAUTIONS: Keep away from children.

===== SECTION X – TRANSPORTATION INFORMATION =====

DOT PROPER SHIPPING NAME: Not Regulated by D.O.T.

DOT HAZARD CLASS: NONE

DOT UN/NA NUMBER: NONE PACKING GROUP: NONE

===== SECTION XI - DISCLAIMER =====

DISCLAIMER:
The information contained herein is based on data available at the time of preparation of this data sheet and which Sashco Inc. believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. Sashco, Inc. shall not be responsible for the use of this information or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment and the health and safety of your employees and users of this material.