

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: STACKER LATEX CAULK (For between logs)
PRODUCT COLORS: Tan, Woodtone

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Sashco, Inc.
ADDRESS: 10300 E. 107th Place, Brighton, CO 80601
EMERGENCY PHONE: 1-800 -535-5053 (Infotrac, Inc.)
INFORMATION PHONE: 1-800 -289 -7290
DATE REVISED: 7-17-99
NAME OF PREPARER: Wayne Summons
CODE IDENTIFICATION: STK
PRODUCT IDENTIFICATION: STACKER, Latex Log Caulking Compound

HMIS Ratings

Health	Flammability	Reactivity
1	0	0

===== SECTION II - HAZARDOUS INGREDIENTS =====

Component	CAS Number	Wt. %	TLV*	LEL**	LD ₅₀ ***	Other
Butyl Benzyl Phthalate	85-68-7	6 - 9	N/A	N/A	20.4g/kg (oral)	None
Dipropylene Glycol Monomethyl ether	34590-94-8	1.3 - 1.6	100 ppm	1.1%	N/A	None
*Ethylene Glycol	107-21-1	.85 - .95	N/A	3.2%	N/A	None
Mineral Spirits	8052-41-3	.75 - .90	100 ppm	1.0%	N/A	None
2[(Hydroxy-methyl)Amino]-2-methyl propanol	52299-80-4	.08 - .10	N/A	N/A	1.04 ml/kg (oral)	None
3-iodo-2-propyneyl butyl carbamate	55406-53-6	.03 - .05	N/A	.6% (@300°F)	2140mg/kg (oral)	None
*Ammonia	7664-41-7	.06 - .09	25 ppm	16%	N/A	300 ppm (IDLH)

*The Threshold Limit Value (TLV) is the time weighted average (TWA) to which it is believed that most workers may be exposed 8-10 hours per day, 40 hours per week, without adverse health effects. **Lower Explosive or Flammability Limit. ***Lethal Dose level for 50% mortality rate among the test animals studied.

This chemical is subject to the reporting requirements of section 313 of SARA Title III.

===== SECTION III - PHYSICAL DATA =====

SPECIFIC GRAVITY (H₂O=1): 1.560 - 1.580 (depending on color)
PERCENT VOLATILE BY VOLUME (%): 29 - 31% (Most of which is water)
EVAPORATION RATE: Approximately that of water
SOLUBILITY IN WATER (cured film): Negligible
SOLUBILITY IN WATER (uncured material): Completely soluble in water until significant drying occurs
APPEARANCE AND ODOR: Fluid paste, slight ammoniacal odor, variety of colors
BOILING POINT (F): N/A
VAPOR PRESSURE (mm Hg.): N/A
VAPOR DENSITY (AIR=1): N/A

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

FLASH POINT (F): N/A
FLAMMABLE LIMITS: N/A
EXTINGUISHING MEDIA: For dried solids, use water, CO₂, foam or dry chemical
SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to cool containers.
UNUSUAL FIRE AND EXPLOSION HAZARDS:

=====**SECTION V - HEALTH HAZARD DATA**=====

THRESHOLD LIMIT VALUE: N/A
EFFECTS OF OVEREXPOSURE: May cause slight irritation of the eyes, skin, nose or throat if material comes in contact with these respective tissues.

EMERGENCY AND FIRST AID PROCEDURES:
If product has been ingested, administer water or milk and contact a physician. If material comes in contact with eyes, rinse thoroughly with water for at least 20 minutes. If irritation persists, contact a physician. If skin contacted, wash with soap and water.

=====**SECTION VI - REACTIVITY DATA**=====

STABILITY: Stable
INCOMPATIBILITY: None known
HAZARDOUS DECOMPOSITION PRODUCTS: None known
HAZARDOUS POLYMERIZATION: Will not occur

=====**SECTION VII - SPILL OR LEAK PROCEDURES**=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
Wipe or scrape up and dispose. No special precautions are required.

WASTE DISPOSAL METHOD:
Dispose in a sanitary landfill (once material has completely dried), or dispose according to local and federal regulations.

=====**SECTION VIII - SPECIAL PROTECTION INFORMATION**=====

RESPIRATORY PROTECTION: None normally needed
VENTILATION: Use maximum ventilation possible, on the interior or exterior.
PROTECTIVE GLOVES: Not normally needed. Latex gloves or other 'tooling' devices may be used to minimize skin contact while finishing. See Section V.
EYE PROTECTION: Not normally needed. See Section V.
OTHER PROTECTIVE EQUIPMENT: None required

=====**SECTION IX - SPECIAL PRECAUTIONS**=====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: It is best to store at room temperature, although short-term freezing can usually be tolerated.
OTHER PRECAUTIONS: Keep away from children.
SHIPPING INFORMATION: Stacker is not regulated under DOT classifications due to posing little or no significant hazards.

=====**SECTION X - DISCLAIMER**=====

DISCLAIMER:
The information contained herein is based on data available at the time of preparation of this data sheet and which Sashco Sealants, Inc. believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The Sashco Corporation shall not be responsible for the use of this information or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment and the health and safety of your employees and of this material.