

**OLYMPIC**  
**OLYLOG**<sup>®</sup>  
 THE BOTTOM LINE IS A BETTER HOME

The Olympic OlyLog is engineered for log home construction

**FEATURES & BENEFITS:**

- No predrilling
- Self countersinking head-style
- Strong pull down and holding power
- Removable
- Corrosion resistant
- No sledge hammer damage
- Greatly reduced labor time
- 100% American Made



**OLYMPIC**  
**BUILDING SYSTEMS PRODUCTS**  
 THE BOTTOM LINE IS A BETTER HOME

CAULKING • CHINKING • STAINS  
 SEALANTS • RESTORATION  
 FINISHES • LOGS • SIDING • RAILINGS  
 FENCING • LOG FURNITURE

AUTHORIZED  
 SASHCO  
 DISTRIBUTOR

*Ozark Log Home Supply*

888-315-7627 TOLL FREE

OZARKLOGHOMES.COM

1621 Porter Wagoner Blvd.  
 West Plains, MO 65775

## THE FEATURES OF THE OLYMPIC OLYLOG® INCLUDE:

- **INSTALLS MUCH FASTER AND EASIER THAN LAGS & SPIKES**
  - SAVES TIME AND FATIGUE
  - DRAMATICALLY LOWERS INSTALLED COST
- **REQUIRES NO PREDRILLING**
  - ELIMINATES ON-SITE PREDRILLING
  - ELIMINATES MANUFACTURING DRILL STATIONS
- **COUNTERSINKS INTO LOG**
  - ALLOWS LOG TO SETTLE NATURALLY
- **DRAWS WARPED LOGS DOWN**
- **REMOVABLE AND REUSABLE**
- **ELIMINATES JARRING AND DAMAGE CAUSED BY A SLEDGE HAMMER**
- **ENGINEERED FOR INCREASED STRENGTH AND PERFORMANCE:**
  - AVERAGE ULTIMATE SHEAR STRENGTH=2995 LBS.
  - AVERAGE OLYLOG PULLOUT STRENGTH=1450 LBS.
    - STRAIGHT SHANK SPIKE=345 LBS.
    - SPIRAL SHANK SPIKE=425 LBS.

**5/16" HEX HEAD**  
(1 FREE DRIVER BIT IN EACH BOX)

**PATENTED HEAD STYLE  
COUNTERSINKS ITSELF  
DURING INSTALLATION.**

**3/16" SHANK DIAMETER**

**MADE OF HEAT TREATED  
STEEL FOR DRAMATICALLY  
INCREASED STRENGTH AND  
DRIVABILITY**

**ULTRA COATED FOR  
UNMATCHED CORROSION  
RESISTANCE**

**2" OF THREAD WITH  
1/4" MAJOR DIAMETER**

**GIMLET POINT FOR  
FAST DRILLING**



### PHYSICAL DATA

Cat. No. Length Thread Length Packaging\* Weight

Thread Diameter: .245	OLOG01902500P	2 1/2"	1 5/8"	500	12 lb
Shank Diameter: .190	OLOG01904000B	4"	2"	250	10 lb
	OLOG01906000B	6"	2"	250	14 lb
Head Style: Hex Head	OLOG01908000B	8"	2"	250	18 lb
	OLOG01909000B	9"	2"	250	20 lb
*Indicates quantity per case. One special hex head driver bit is included in each box.	OLOG01910000B	10"	2"	250	23 lb
	OLOG01912000B	12"	2"	250	25 lb
	OLOG01914000B	14"	2"	250	29 lb
	OLOG01916000B	16"	2"	250	36 lb

### INSTALLATION INSTRUCTIONS

- USE A 1/2", HIGH TORQUE, LOW RPM DRILL.
- INSTALL OLYLOG PERPENDICULAR TO THE LOG.
- COUNTERSINK THE OLYLOG A MINIMUM OF 1/4".

### OTHER OLYLOG USES

- DOVETAIL ATTACHMENTS
- POST & BEAM CONSTRUCTION
- BEAMS AND RAFTERS
- AND MUCH MORE